















Category		Model	Product Description
WLAN		AP673	Settled AP Wi-Fi 7 13.66 Gbps device rate Tri-radio 300 access users recommended Max. 1024 access users 26 dBm transmit power 1 x 100M/GE/2.5GE/5GE electrical port, 1 x 10M/100M/GE electrical port, 1 x USB port Smart antenna 30 m optimal coverage range
		AP362E	Settled AP Wi-Fi 6 2.975 Gbps device rate Dual-radio 100 access users recommended Max. 128 access users 23 dBm transmit power Smart antenna 20 m optimal coverage range GE (RJ45) x 1, 10M/100M/1000M auto-sensing
		AP265E	Wall plate AP Wi-Fi 6 2.975 Gbps device rate Dual-radio 64 access users recommended Max. 128 access users 23 dBm transmit power 4 x GE electrical ports PoE Smart antenna leader AP 13 m optimal coverage ranges
		AP266	Wall plate AP Wi-Fi 6 2.975 Gbps device rate Dual-radio 64 access users recommended Max. 128 access users 23 dBm transmit power 4 x GE electrical ports PoE Smart antenna leader AP 13 m optimal coverage range one POE Out
		AP162E	Wall plate 86x86 AP Wi-Fi 6 2.975 Gbps device rate Dual-radio 48 access users recommended Max. 128 access users 20 dBm transmit power Smart antenna 10 m optimal coverage range 1 x GE uplink electrical port + 1 x GE downlink electrical port.
		AP371	Settled AP Wi-Fi 7 3.57 Gbps device rate Dual-radio 150 access users recommended Max. 256 access users 23 dBm transmit power Smart antenna 18 m optimal coverage range 1 x 2.5GE uplink electrical port
		AP361	Settled AP Wi-Fi 6 802.11ax 1.775 Gbps device rate Dual-radio 80 access users recommended Max. 128 access users 20 dBm transmit power Smart antenna 18 m optimal coverage range 1 x GE uplink electrical port
		AP263	Wall plate AP Wi-Fi 6 802.11ax 2.975 Gbps device rate Dual-radio 64 access users recommended Max. 256 access users 23 dBm transmit power 1 x GE electrical ports Smart antenna leader AP 13 m optimal coverage range
		AP661(High-density)	Settled AP Wi-Fi 6 6.575 Gbps device rate Tri-radio 300 access users recommended Max. 1536 access users 26 dBm transmit power 2.5 GE electrical port 1 GE electrical port Smart antenna 40 m optimal coverage range USB,BLE
		AP761(Outdoor)	Out-door AP Wi-Fi 6 1.775 Gbps device rate Dual-radio 120 access users recommended Max. 1024 access users 28 dBm transmit power 1 GE electrical port 1 SFP optical port Smart antenna 500 m optimal coverage distance
		AC650-128AP	wireless access controller Manage APs: 128 10 x 10/100/1000BASE-T ports, 2 x 10 GE SFP+ ports with the AC/DC adapter)
		AC650-256AP	wireless access controller Manage APs: 256 10 x 10/100/1000BASE-T ports, 2 x 10 GE SFP+ ports with the AC/DC adapter)
		AC650-512AP	wireless access controller Manage APs: 512 10 x 10/100/1000BASE-T ports, 2 x 10 GE SFP+ ports with the AC/DC adapter)
Unmanaged Switch		S110-8P2ST	8 x 10/100/1000BASE-T ports, 1 x GE SFP port, 1 x 10/100/1000BASE-T port PoE+ 124W Packet forwarding rate: 14.88 Mpps Switching capacity: 20 Gbit/s, AC power, power adapter)
		S110-8T2ST	8 x 10/100/1000BASE-T ports, 1 x GE SFP port, 1 x 10/100/1000BASE-T port Packet forwarding rate: 14.88 Mpps Switching capacity: 20 Gbit/s, with 7*AC power adapter, fanless)
		S110-16LP2SR	16 x 10/100/1000BASE-T ports, 2 x GE SFP ports PoE+ 124 W Packet forwarding rate: 26.78 Mpps Switching capacity: 36 Gbit/s AC power
		S110-16T2S	16 x 10/100/1000BASE-T ports, 2 x GE SFP ports Packet forwarding rate: 26.78 Mpps Switching capacity: 36 Gbit/s, built-in AC power, fanless)
		S110-24LP2SR	24 x 10/100/1000BASE-T ports, 2 x GE SFP ports PoE+ 124 W Packet forwarding rate: 38.69 Mpps Switching capacity: 52 Gbit/s, AC power
		S110-24T2SR	24 x 10/100/1000BASE-T ports, 2 x GE SFP ports Packet forwarding rate: 38.69 Mpps Switching capacity: 52 Gbit/s, AC power
L2 Managed Switch		S220-8T4S	8 x 10/100/1000BASE-T, 4 x GE SFP ports built-in AC power Packet forwarding rate: 18 Mpps Switching capacity: 24 Gbit/s, AC power
		S220-8P4S	8 x 10/100/1000BASE-T, 4 x GE SFP ports 125W PoE+ built-in AC power Packet forwarding rate: 18 Mpps Switching capacity: 24 Gbit/s built-in AC power
		S220-24T4X	24 x 10/100/1000BASE-T ports, 4 x 10GE SFP+ ports built-in AC power Packet forwarding rate: 95 Mpps Switching capacity: 128 Gbit/s, built-in AC power
		S220-24P4X(400W)	24 x 10/100/1000BASE-T ports, 4 x 10GE SFP+ ports 400W PoE+ built-in AC power Packet forwarding rate: 95 Mpps Switching capacity: 128 Gbit/s built-in AC power
		S220-48T4X	48 x 10/100/1000BASE-T ports, 4 x 10GE SFP+ ports built-in AC power Packet forwarding rate: 131 Mpps Switching capacity: 176 Gbit/s, built-in AC power
		S220-48T4S	48 x 10/100/1000BASE-T ports, 4 x GE SFP ports built-in AC power Packet forwarding rate: 77 Mpps Switching capacity: 104 Gbit/s, built-in AC power
		S220-48P4X(380W)	48 x 10/100/1000BASE-T ports, 4 x 10GE SFP+ ports 380W PoE+ built-in AC power Packet forwarding rate: 131 Mpps Switching capacity: 176 Gbit/s, built-in AC power
		S220-48P4S(380W)	48 x 10/100/1000BASE-T ports, 4 x GE SFP ports 380W PoE+ built-in AC power Packet forwarding rate: 77 Mpps Switching capacity: 104 Gbit/s, built-in AC power
		S220S-8T2J	8 x 10/100/1000BASE-T ports, 2 x 2.5GE SFP ports Packet forwarding rate: 19 Mpps Switching capacity: 26 Gbit/s, built-in AC power, Fanless
		S220S-8T2X	8 x 10/100/1000BASE-T ports, 2 x 10GE SFP+ ports Packet forwarding rate: 42 Mpps Switching capacity: 56 Gbit/s, built-in AC power, Fanless)
		S220S-8P4J	8 x 10/100/1000BASE-T PoE+ ports 128 W PoE, 4 x 2.5GE SFP ports Packet forwarding rate: 27 Mpps Switching capacity: 36 Gbit/s +, built-in AC power, Fanless)
		S220S-8P4JX	8 x 10/100/1000BASE-T PoE+ 128 W ports, 2 x 10GE SFP+ ports, 2 x 2.5GE SFP ports Packet forwarding rate: 49 Mpps Switching capacity: 66 Gbit/s, built-in AC power, Fanless

		S220S-10PN4JX	6 x 10/100/1000BASE-T PoE+ ports, 2 x 10/100/1000BASE-T ports, 2 x 10M/100M/GE/2.5GE BASE-T PoE+ ports (multi-GE ports), 2 x 10GE SFP+ ports, 2 x 2.5GE SFP ports Packet forwarding rate: 57 Mpps Switching capacity: 76 Gbit/s , built-in AC power, Fanless
		S220S-24T4J	24 x 10/100/1000BASE-T ports, 4 x 2.5GE SFP ports Packet forwarding rate: 51 Mpps Switching capacity: 68 Gbit/s, built-in AC power, Fanless
		S220S-24T4JX	24 x 10/100/1000BASE-T ports, 2 x 10GE SFP+ ports, 2 x 2.5GE SFP ports Packet forwarding rate: 73 Mpps Switching capacity: 98 Gbit/s, built-in AC power, Fanless
		S220S-24P4J	24 x 10/100/1000BASE-T PoE+ ports, 4 x 2.5GE SFP ports Packet forwarding rate: 51 Mpps Switching capacity: 68 Gbit/s (400 W PoE+), built-in AC power
		S220S-24LP4JX	24 x 10/100/1000BASE-T ports, 2 x 10GE SFP+ ports, 2 x 2.5GE SFP ports Packet forwarding rate: 73 Mpps Switching capacity: 98 Gbit/s (195 W PoE+), 2*10GE SFP+ ports, built-in AC power
		S220S-26PN4JX	22 x 10/100/1000BASE-T PoE+ ports, 2 x 10/100/1000BASE-T ports, 2*10/100/1000/2.5GBASE-T Combo(PoE+), 2 x 10GE SFP+ ports Packet forwarding rate: 73 Mpps Switching capacity: 98 Gbit/s 400 W PoE , built-in AC power
L2+ Managed Switch		S310S-8T2X	8 x 10/100/1000BASE-T ports, 2 x 10GE SFP+ ports Packet forwarding rate: 42 Mpps Switching capacity: 56 Gbit/s, built-in AC power, Fanless
		S310S-8P4JX	8 x 10/100/1000BASE-T PoE+ ports, 2 x 10GE SFP+ ports, 2 x 2.5GE SFP ports Packet forwarding rate: 49 Mpps Switching capacity: 66 Gbit/s (128 W PoE+), built-in AC power, Fanless
		S310S-10PN4JX	6 x 10/100/1000BASE-T PoE+ ports, 2 x 10/100/1000BASE-T ports, 2 x 10M/100M/GE/2.5GE BASE-T PoE+ ports (multi-GE ports), 2 x 10GE SFP+ ports, 2 x 2.5GE SFP ports Packet forwarding rate: 56 Mpps Switching capacity: 76 Gbit/s 128 W PoE , built-in AC power, Fanless
		S310S-24T4J	24 x 10/100/1000BASE-T ports, 4 x 2.5GE SFP ports Packet forwarding rate: 51 Mpps Switching capacity: 68 Gbit/s built-in AC power, Fanless
		S310S-24T4JX	24 x 10/100/1000BASE-T ports, 2 x 10GE SFP+ ports, 2 x 2.5GE SFP ports Packet forwarding rate: 73 Mpps Switching capacity: 98 Gbit/s
		S310S-24P4J	24 x 10/100/1000BASE-T PoE+ ports, 4 x 2.5GE SFP ports Packet forwarding rate: 51 Mpps Switching capacity: 68 Gbit/s (400 W PoE+) built-in AC power
		S310S-24P4JX	24 x 10/100/1000BASE-T PoE+ ports, 2 x 10GE SFP+ ports, 2 x 2.5GE SFP ports PoE Packet forwarding rate: 73 Mpps Switching capacity: 98 Gbit/s(400 W PoE+) built-in AC power
		S310S-26PN4JX	22 x 10/100/1000BASE-T PoE+ ports, 2 x 10/100/1000BASE-T ports, 2*10/100/1000/2.5GBASE-T Combo(PoE+), 2 x 10GE SFP+ ports Packet forwarding rate: 73 Mpps Switching capacity: 98 Gbit/s 400 W PoE , built-in AC power
		S310-24ST4X	24 x GE SFP ports, 8 of which are dual-purpose 10/100/1000 or SFP, 4*10GE SFP+ ports built-in AC power Packet forwarding rate: 96 Mpps Switching capacity: 128 Gbit/s
		S310-24PN4X	24 x 10/100/1000/2.5GBASE-T ports(400W PoE+), 4*10GE SFP+ ports Built-in AC power Packet forwarding rate: 144 Mpps Switching capacity: 200 Gbit/s
		S310-48T4S	48 x 10/100/1000BASE-T ports, 4 x GE SFP ports AC power supply Packet forwarding rate: 77 Mpps Switching capacity: 104 Gbit/s ,
		S310-24T4S	24 x 10/100/1000BASE-T ports, 4 x GE SFP ports AC power supply Packet forwarding rate: 42 Mpps Switching capacity: 56 Gbit/s
		S310-24P4S	24 x 10/100/1000BASE-T ports, 4 x GE SFP ports AC power supply 400 W PoE+ Packet forwarding rate: 42 Mpps Switching capacity: 56 Gbit/s
		S310-24T4X	24 x 10/100/1000BASE-T ports, 4 x 10GE SFP+ ports AC power supply Packet forwarding rate: 95 Mpps Switching capacity: 128 Gbit/s built-in AC power
		S310-24P4X(400W)	24 x 10/100/1000BASE-T ports, 4 x 10GE SFP+ ports AC power supply PoE+ Packet forwarding rate: 95 Mpps Switching capacity: 128 Gbit/s(400W PoE+)+ ports, built-in AC power
		S310-48T4X	48 x 10/100/1000BASE-T ports, 4 x 10GE SFP+ ports AC power supply Packet forwarding rate: 131 Mpps Switching capacity: 176 Gbit/s built-in AC power
		S310-48P4X	(48 x 10/100/1000BASE-T ports, 4 x 10GE SFP+ ports AC power supply PoE+ Packet forwarding rate: 131 Mpps Switching capacity: 176 Gbit/s 380W PoE+) built-in AC power
		S310-48P4S(380W)	48 x 10/100/1000BASE-T ports, 4 x GE SFP ports AC power supply PoE+ Packet forwarding rate: 77 Mpps Switching capacity: 104 Gbit/s(380W PoE+) built-in AC power
L3 Managed Switch		S530-48S4XE	48 x GE SFP ports, 4 x 10GE SFP+ ports, 2 x 10GE stack ports Packet forwarding rate: 168 Mpps Switching capacity: 224 Gbit/s, with 1*AC power module
		S530-24ST4XE	24 x GE SFP ports, 8 of which are dual-purpose 10/100/1000 or SFP, 4 x 10GE SFP+ ports, 2 x 10GE stack ports Packet forwarding rate: 132 Mpps Switching capacity: 176 Gbit/s with 1*AC power module
		S530-24T4XE	24 x 10/100/1000BASE-T ports, 4 x 10GE SFP+ ports, 2 x 10GE stack ports Packet forwarding rate: 132 Mpps Switching capacity: 176 Gbit/s with 1*AC power module
		S620-24T16X8Y2CZ	24 x 10/100/1000M BASE-T ports, 16 x 10GE SFP+ ports, 8 x 25GE SFP28 ports, 2 x 40GE/100GE QSFP28 Packet forwarding rate: 867 Mpps Switching capacity: 1168 Gbit/s, expansion card slot, with 1*AC power module
Gateway		S380-H8T3ST	Multi-Service Gateway Number of managed Aps: 128 Maximum user: 500 Switching Capacity: 16Gbps Packet forwarding rate: Upload:500 Kpps, download:420 Kpps Egress bandwidth: 2Gbps 2 x 10/100/1000BASE-T ports, 1 x GE SFP port(WAN) + 8 x 10/100/1000BASE-T ports(LAN)
		S380-S8P2T	Multi-Service Gateway Number of managed Aps: 64 Maximum user: 300 Switching Capacity: 16Gbps Packet forwarding rate: Upload:500 Kpps, download:420 Kpps Egress bandwidth: 2Gbps 2 x 10/100/1000BASE-T ports(WAN),8 x 10/100/1000BASE-T ports(LAN) PoE+ 124W
		S380-S8T2T	Multi-Service Gateway Number of managed Aps: 64 Maximum user: 300 Switching Capacity: 16Gbps Packet forwarding rate: Upload:500 Kpps, download:420 Kpps Egress bandwidth: 2Gbps 2 x 10/100/1000BASE-T ports(WAN) + 8 x 10/100/1000BASE-T ports(LAN)
		S380-L4P1T	Multi-Service Gateway Number of managed Aps: 32 Maximum user: 200 Switching Capacity: 8Gbps Packet forwarding rate: Upload:300 Kpps, download:420 Kpps Egress bandwidth: 1Gbps 1 x 10/100/1000BASE-T port(WLAN) + 4 x 10/100/1000BASE-T ports(LAN) PoE+, 50W

		S380-L4T1T	Multi-Service Gateway Number of managed Aps: 32 Maximum user: 200 Switching Capacity: 8Gbps Packet forwarding rate: Upload:300 Kpps, download:420 Kpps Egress bandwidth: 1Gbps 1 x 10/100/1000BASE-T port(WAN)+4 x 10/100/1000BASE-T ports(LAN)
		AR303W	Router,AR303W, 1*GE COMBO WAN, 4*GE LAN, 1*USB 2.0, Wi-Fi 2.4G+5G
		AR303	Desktop router 200 client devices Packet forwarding rate: 1Mpps 4 x GE electrical ports(LAN), 1*GE Combo(WAN)
		AR720	Forwarding performance: 9 Mpps to 25 Mpps Number of connected terminals: 700 Fixed WAN ports: 2 x GE combo ports Fixed LAN ports: 8 x GE ports (can be switched to WAN ports) Dimensions (H x W x D): 43.6 mm x 442 mm x 220 mm, 2*USB 2.0, 2*SIC
		AR730	Forwarding performance: 9 Mpps to 25 Mpps Number of connected terminals: 1200 Fixed WAN ports: 2 x GE combo ports, 1 x 10GE optical port (compatible with GE optical) Fixed LAN ports: 1 x GE combo port, 8 x GE electrical ports (can be switched to WAN ports) Dimensions (H x W x D): 43.6 mm x 442 mm x 220 mm, 2*USB 2.0, 2*SIC
Accessories		OSX040N01	Optical Transceiver,SFP+,10G,Single-mode Module(1550nm,40km,LC)
		SFP-10G-USR	10GBase-USR Optical Transceiver,SFP+,10G,Multi-mode Module(850nm,0.1km,LC)
		SFP-10G-CU1M	SFP+,10G,High Speed Direct-attach Cables,1m,SFP+20M,CC2P0.254B(S),SFP+20M,Used indoor
		SFP-10G-CU3M	SFP+,10G,High Speed Direct-attach Cables,3m,SFP+20M,CC2P0.254B(S),SFP+20M,Used indoor
		SFP-10G-AOC10M	AOC Optical Transceiver,SFP+,850nm,1G~10G,10m
		SFP-10G-ZR	10GBase-ZR Optical Transceiver,SFP+,10G,Single-mode Module(1550nm,80km,LC)
		SFP-10G-iLR	Optical Transceiver,SFP+,9.8G,Single-mode Module(1310nm,1.4km,LC)
		SFP+STACK-CU0M5	SFP+ High speed dedicated stack cable-0.5m
		SFP+STACK-CU1M5	SFP+ High speed dedicated stack cable-1.5m
		SFP-1000BaseT	Electrical Transceiver,SFP,GE,Electrical Interface Module(100m,RJ45)
		SFP-GE-LX-SM1310	Optical Transceiver,eSFP,GE,Single-mode Module(1310nm,10km,LC)
		eSFP-GE-SX-MM850	Optical Transceiver,eSFP,GE,Multi-mode Module(850nm,0.55km,LC)
		eSFP-FE-LX-SM1310	Optical Transceiver,eSFP,100M/155M,Single-mode Module(1310nm,15km,LC)
		S-SFP-GE-LH40-SM1310	Optical Transceiver,eSFP,GE,Single-mode Module(1310nm,40km,LC)
		S-SFP-GE-LH40-SM1550	Optical Transceiver,eSFP,GE,Single-mode Module(1550nm,40km,LC)
		S-SFP-GE-LH80-SM1550	Optical Transceiver,eSFP,GE,Single-mode Module(1550nm,80km,LC)
		OMXD30000	Optical Transceiver,SFP+,10G,Multi-mode Module(850nm,0.3km,LC)
		OSX010000	Optical Transceiver,SFP+,10G,Single-mode Module(1310nm,10km,LC)
		HW-120200E5W	AC-DC 24W/12V Adaptor(EU) AC-DC 24W/12V Adapter(EU,applicable to AP263 and AP362)
		AD-560062T0E	POE Adapter Power-AD-560062T0E-Desktop-35W-efficiency 85%POE Adapter Power-AD-560062T0E-Desktop-35W-efficiency 85% (applicable to AP160, AP361, AP362, and AP263)